

Impact-Rated Doors



Simpson now offers hundreds of impact-rated exterior doors, suitable for coastal applications that require it. Please note: these doors do not have HVHZ approval at this time.

Specifications:

- Labeled Prehung Units available both assembled and knocked down (KD)
- Impact-rated slabs available for specialty prehangs
- Choose any design from Simpson’s exterior door offering
- Available in any wood type
- Impact-rated IG used with many textures available, including turtle glass
- Profiles available: ovolo, shaker, bevel
- Panel types: available in any profile/raise
- All doors offered 2-1/4” thick
- Inswing Single Doors
 - » Max Unit or Slab-Only Size, All-Panel Doors: 3’6” x 9’0”
 - » Max Unit or Slab-Only Size, Doors with Glass: 3’6” x 9’0”
- Outswing Single Doors
 - » Max Unit Size (All doors): 4’0” x 10’0”
 - » Max Slab-Only Size: 4’0” x 10’0”
- Inswing Double Doors (Square Top Only)
 - » Max Unit Size: 7’0” x 9’0”
- Outswing Double Doors
 - » Max Unit Size, Square Top Doors: 8’0” x 10’0”
 - » Max Unit Size, Arch and Radius Top Doors: 7’0” x 10’0”
- Sidelights and Transoms
 - » Can be added to any single or double door unit
 - » Arched and elliptical transoms available
 - » Max Sidelight Size: 3’0” x 8’0”
 - » Max Transom Size: 6’0” x 3’0”
- Multi-Point Locks*
 - » Required for all impact-rated doors
 - » Choose from Hoppe 9000 or Endura Trillanium brands
 - » Single door units = 3-point (Tongue top, tongue bottom, deadbolt)
 - » Double Door Units = 5-point (Tongue top, tongue bottom, shootbolts head and sill, deadbolt for active door. Tongue top, tongue bottom for inactive door)
- Sills
 - » All units provided with composite adjustable sill

*Additional hardware may be required in some specific applications.

NAMI

NAMI certified and approved for all coastal areas from Maine to Texas (except HVHZ)



Florida Code Report,
#FL9668, #FL14487 (Structural),
#FL14488 (Structural), #FL23103,
#FL39328, #FL39330

Simpson®
Door Company

