



- · Patented precision design with integral panels provides uniform structural support.
- · Seamless stile and rail with no possibility of separation.
- · Will not shrink, split, warp or move.
- Doors are available in 1-3/4" or 1-3/8" thickness and feature tempered hardboard surface.
- · Internal stiles have one-inch width with finger joint wood for ultimate screwholding performance.
- · Moisture resistant Type 1 glue internal construction.
- · Solid continuous particleboard core.
- · Raised or flush moldings installed to precision tolerances (.030 inch).
- · Primed all six sides and ready to paint.
- · One of both sides with molding or separate designs on each side.
- Customized designs are available. Our engineering lab will review all designs.
- · Quality crafted with environmentally friendly materials in the United States.
- Door edges are beveled on both sides with a three degree bevel.

FIRE RATING

- · 20 minute fire rating is included on all square top 1-3/4" Infinity Doors in sizes up to 8'-0".
- Positive pressure fire ratings of up to 60 minutes are available for selected units with raised panels.
- · For more detailed fire rating information, contact Simpson Door Company.

SPECIFICATIONS

1-3/4" THICKNESS:

2'0", 2'4", 2'6", 2'8, 2'10", 3'0", 3'6", 4'0" WIDTHS:

HEIGHTS: 6'8", 7'0", 8'0", 9'0"


10"

STILES: 5-3/8" TOP RAIL: 4-7/8"


BOTTOM RAIL:



Raised Molding Profile



Flush Molding Profile







R: Raised Molding F: Flush Molding

Simpson[®]

400 Simpson Ave. • McCleary, WA 98557 • 1-800-952-4057 simpsondoor.com